


## Product range

It is possible to hot dip galvanise the full range detailed below.



SIZE OF THREAD R (inches)	SPECIFIED OUTSIDE DIAMETER D (mm)	SERIES M		SERIES H		TYPE L1		TYPE L2		TYPE L	
		THICKNESS (mm)	MASS (kg/m)	THICKNESS (mm)	MASS (kg/m)	THICKNESS (mm)	MASS (kg/m)	THICKNESS (mm)	MASS (kg/m)	THICKNESS (mm)	MASS (kg/m)
1/4	13.5	-	-	-	-	-	-	-	-	2.0	0.567
3/8	17.2	2.3	0.839	2.9	1.02	2.0	0.742	1.8	0.670	2.0	0.750
1/2	21.3	2.6	1.21	3.2	1.44	2.3	1.08	2.0	0.947	2.3	1.08
3/4	26.9	2.6	1.56	3.2	1.87	2.3	1.39	2.3	1.38	2.3	1.40
1	33.7	3.2	2.41	4.0	2.93	2.9	2.20	2.6	1.98	2.9	2.20
1 1/4	42.4	3.2	3.10	4.0	3.79	2.9	2.82	2.6	2.54	2.9	2.82
1 1/2	48.3	3.2	3.56	4.0	4.37	2.9	3.24	2.9	3.23	2.9	3.25
2	60.3	3.6	5.03	4.0	6.19	3.2	4.49	2.9	4.08	3.2	4.51
2 1/2	76.1	3.6	6.42	4.5	7.93	3.2	5.73	3.2	5.71	3.2	5.75
3	88.9	4.0	8.36	5.0	10.3	3.6	7.55	3.2	6.72	3.2	6.76
3 1/2	101.6	-	-	-	-	-	-	-	-	3.6	8.70
4	114.3	4.5	12.2	5.4	14.5	4.0	10.8	3.6	9.75	3.6	9.83
5	139.7	5.0	16.6	5.4	17.9	-	-	-	-	4.5	15.0
6	165.1	5.0	19.8	5.4	21.3	-	-	-	-	4.5	17.8

\* mass per unit of length of black tube with flat end.

Moreover, tubes can be manufactured under the EN 10219 standard and hot dip galvanised under the EN 10240 standard, in the following range.

DIAMETER		THICKNESS (mm)	MASS (Kg/m)
Inches	mm		
7	177.8	3	14.10
		4	18.70
		5	23.30
		6	27.80
8	203.2	3	16.00
		4	21.20
		5	26.40
		6	31.50
10	254.0	4	26.50
		5	33.00
		6	39.50
12	304.8	4	31.60
		5	39.30
		6	47.00